



MINIBAR & REFRIGERATION TECHNOLOGY



Experience the cool of silence

www.ismminibar.com

MiniMax Solutions

SERIE PLATINUM

STANDARD FEATURES

- The use of C-pentan (100% environment-friendly)
- Absorption cooling system
- ISM logic thermostat
- Automatic defrost
- Interior led light
- Reversible door
- Blue transparent shelves
- Curved door
- 1.5 lt Bottle holder (40 lt/52 lt/60 lt)

OPTIONAL FEATURES

- Energy supply (110V/60Hz-12/230V-12/110V-24/230V)
- Lock
- Wheels
- Mdf door
- Glass door
- Chromium door
- Sliding hinge for build in models
- Free standing
- Built in
- Ice cube

COLOR RANGE



Black



White



Dark Brown



Teka



Oak



Sapeli



Grey
(Metallic)



→ SM 301



→ SM 401





→ SM 601



SERIE PLATINUM



→ SM 401-06



→ SM 401 Monoblok



→ SM 521-C




MODEL	SM 301	SM 401	SM 521	SM 601
Gross Volume	30 Lt	38 Lt	43 Lt	54 Lt
Net Volume	26 Lt	33 Lt	38 Lt	48 Lt
External Dimensions (H-W-D)	512 mm x 419 mm x 423 mm	566 mm x 441 mm x 457 mm	610 mm x 441 mm x 457 mm	566 mm x 477 mm x 522 mm
Packed Dimensions (H-W-D)	559 mm x 442 mm x 464 mm	614 mm x 464 mm x 494 mm	659 mm x 464 mm x 494 mm	623 mm x 499 mm x 554 mm
Compartment Type	Cellar	Cellar	Cellar	Cellar
Energy Consumption (kWh / Annum)	256	263	270	270
Energy Class	D	D	D	D
Energy Efficiency Index	102,6	105,1	107,7	107,1
Climate Class	N (16°C - 32°C)	N (16°C - 32°C)	N (16°C - 32°C)	N (16°C - 32°C)
Gross Weight	13,4 kg	15,4 kg	16,6 kg	17,7 kg
Net Weight	12,1 kg	14 kg	15 kg	16 kg
Power	60-75 Watt	60-75 Watt	60-75 Watt	75 Watt
Power Supply	230 V / 50-60 Hz	230 V / 50-60 Hz	230 V / 50-60 Hz	230 V / 50-60 Hz
Container Loading Capacity (20"/40"/40"HC)	260 - 540 - 540	165 - 360 - 480	165 - 360 - 480	132 - 276 - 368

This product is compatible to EU directives: 643 / 2009 and 1060 / 2010.
Products are tested according to EN ISO 15502 standards.



Sliding hinge fixture
for built-in models



Crystal shelves



Lock (Optional)



Wheels (Optional)



Intelligent LED light



Reversible door



1.5 lt Bottle holder
(40 lt/52 lt/60 lt)



→ SM 301-G



→ SM 401-G